

# ggmap : Spatial Visualization with ggplot2

by David Kahle and Hadley Wickham

**Abstract** In spatial statistics the ability to visualize data and models superimposed with their basic social landmarks and geographic context is invaluable. **ggmap** is a new tool which enables such visualization by combining the spatial information of static maps from Google Maps, OpenStreetMap, Stamen Maps or CloudMade Maps with the layered grammar of graphics implementation of **ggplot2**. In addition, several new utility functions are introduced which allow the user to access the Google Geocoding, Distance Matrix, and Directions APIs. The result is an easy, consistent and modular framework for spatial graphics with several convenient tools for spatial data analysis.

## Introduction

Visualizing spatial data in R can be a challenging task. Fortunately the task is made a good deal easier by the data structures and plot methods of **sp**, **RgoogleMaps**, and related packages (Pebesma and Bivand, 2006), (Bivand, Pebesma, and Gomez-Rubio, 2008), (Loecher and Sense Networks, 2010). Using those methods, one can plot the basic geographic information of (for instance) a shape file containing polygons for areal data or points for point referenced data. However, compared to specialized geographic information systems (GISs) such as ESRI's ArcGIS, which can plot points, polygons, etc. on top of maps and satellite imagery with drag-down menus, these visualizations can be pretty disappointing. This article details some new methods for the visualization of spatial data in R using the layered grammar of graphics implementation of **ggplot2** in conjunction with the contextual information of static maps from Google Maps, OpenStreetMap, Stamen Maps or Cloudmade Maps (Wickham, 2009) (Wickham, 2010). The result is an easy to use R package named **ggmap**. After describing the nuts and bolts of **ggmap**, we showcase some of its capabilities in a simple case study concerning violent crimes in downtown Houston, Texas and present an overview of a few utility functions.

## Plotting spatial data in R

Areal data is data which corresponds to geographical extents with polygonal boundaries. A typical example is the number of residents per zip code. Considering only the boundaries of the areal units, we are

used to seeing areal plots in R which resemble Figure 1.




Figure 1: Typical R areal plot – zip codes in the Greater Houston area

While these kinds of plots are useful, they are not as informative as we would like in many situations. For instance, when plotting zip codes it is helpful to also see major roads and other landmarks which form the boundaries of areal units.

The situation for point referenced spatial data is often much worse. Since we can't easily contextualize a scatterplot of points without any background information at all, it is common to add points as an overlay of some areal data—whatever areal data is available. The resulting plot looks like Figure 2.





Figure 2: Typical R spatial scatterplot – murders in Houston from January 2010 to August 2010

In most cases the plot is understandable to the researcher who has worked on the problem for some time but is of hardly any use to his audience, who must work to associate the data of interest with their location. Moreover, it leaves out many practical details—are most of the events to the east or west of landmark  $x$ ? Are they clustered around more well-to-do parts of town, or do they tend to occur in disadvantaged areas? Questions like these can't really be answered using these kinds of graphics because we don't think in terms of small scale areal boundaries (e.g. zip codes or census tracts).

This is of course a (gross) exaggeration. With a little effort better plots can be made, and tools such as **maps**, **maptools**, **sp**, and **RgoogleMaps** make the process much easier; in fact, **RgoogleMaps** was the inspiration for **ggmap**. Moreover there has recently been a deluge of interest in the subject of mapmaking in R—Ian Fellows' excellent interactive GUI-driven **DeducerSpatial** package based on Bing Maps comes to mind. **ggmap** takes another step in this direction by situating the contextual information of various kinds of static maps in the **ggplot2** plotting framework. The result is an easy, consistent way of specifying plots which are readily interpretable by both expert and audience and safeguarded from graphical inconsistencies by the layered grammar of graphics framework. The result is a spatial plot resembling Figure 3.

```
murder <- subset(crime, offense == "murder")

qplot(lon, lat, data = murder,
      colour = I('red'), size = I(3), darken = .3)
```



`plot2`, and then plot additional content layers of data, statistics, or models on top of the map. In `ggmap` this process is broken into two pieces – (1) downloading the images and formatting them for plotting, done with `get_map`, and (2) making the plot, done with `ggmap`. `qmap` marries these two functions for quick map plotting (c.f. `ggplot2`'s `ggplot`), and `qmapplot` attempts to wrap up the entire plotting process into one simple command (c.f. `ggplot2`'s `qplot`).

## The `get_map` function

In `ggmap`, downloading a map as an image and formatting the image for plotting is done with the `get_map` function. More specifically, `get_map` is a wrapper function for the underlying functions `get_googlemap`, `get_openstreetmap`, `get_stamenmap`, and `get_cloudmademap` which accepts a wide array of arguments and returns a classed raster object for plotting with `ggmap`.

As the most important characteristic of any map is location, the most important argument of `get_map` is the `location` argument. Ideally, `location` is a longitude/latitude pair specifying the center of the map and accompanied by a `zoom` argument, an integer from 3 to 20 specifying how large the spatial extent should be around the center, with 3 being the continent level and 20 being roughly the single building level. `location` is defaulted to downtown Houston, Texas, and `zoom` to 10, roughly a city-scale.

While longitude/latitude pairs are ideal for specifying a location, they are somewhat inconvenient on a practical level. For this reason, `location` also accepts a character string. The string, whether containing an address, zip code, or proper name, is then passed to the `geocode` function which then determines the appropriate longitude/latitude coordinate for the center. In other words, there is no need to know the exact longitude/latitude coordinates of the center of the map—`get_map` can determine them from more colloquial ("lazy") specifications so that they can be specified very loosely. For example, since

```
> geocode("the white house")
      lon      lat
-77.03676 38.89784
```


works, "the white house" is a viable location argument. More details on `geocode` and other utility functions are discussed at the end of this article.

In lieu of a center/zoom specification, some users find a bounding box specification more convenient. To accommodate this form of specification, `location` also accepts numeric vectors of length four following the left/bottom/right/top convention. This option is not currently available for Google Maps.

While each map source has its own web application programming interface (API), the `location/zoom` specification in `get_map` works for each by computing the appropriate parameters (if

necessary) and passing them to each of the API specific `get_*` functions. To ensure that the resulting maps are the same across the various sources for the same `location/zoom` specification, `get_map` first grabs the appropriate Google Map, determines its bounding box, and then downloads the other map as needed. In the case of Stamen Maps and Cloudmade Maps, this involves a stitching process of combining several tiles (small map images) and then cropping the result to the appropriate bounding box. The result is a single, consistent specification syntax across the four map sources as seen for Google Maps and OpenStreetMap in Figure 4.

```
baylor <- "baylor university"
qmap(baylor, zoom = 14)
```



```
qmap(baylor, zoom = 14, source = "osm")
```




Figure 4: `get_map` provides the same spatial extent for Google Maps (top) and OpenStreetMaps (bottom) with a single simple syntax, even though their APIs are quite different



Before moving into the `source` and `maptype` arguments, it is important to note that the underlying API specific `get_*` functions for which `get_map` is a wrapper provide more extensive mechanisms for downloading from their respective sources. For example, `get_googlemap` can access almost the full range of the Google Static Maps API as seen in Figure 5.

```
set.seed(500)
df <- round(data.frame(
  x = jitter(rep(-95.36, 50), amount = .3),
  y = jitter(rep(29.76, 50), amount = .3)
), digits = 2)

map <- get_googlemap('houston', markers = df,
  path = df, scale = 2)

ggmap(map, extent = 'device')
```




Figure 5: Accessing Google Maps API features with `get_googlemap`

**Tile style - the `source` and `maptype` arguments of `get_map`**


The most attractive aspect of using different map sources (Google Maps, OpenStreetMap, Stamen Maps, and Cloudmade Maps) is the different map styles provided by the producer. These are specified with the `maptype` argument of `get_map` and must agree with the `source` argument. Some styles emphasize large roadways, others bodies of water, and still others political boundaries. Some are better for plotting in a black-and-white medium; others are simply nice to look at. This section gives a run down of the various map styles available in **ggmap**.

Google provides four different familiar types—terrain (default), satellite (e.g. Figure 16), roadmap, and hybrid (e.g. Figure 15). OpenStreetMap, on the

other hand, only provides the default style shown in Figure 4.

Style is where Stamen Maps and Cloudmade Maps really shine. Stamen Maps has three available tile sets—terrain (e.g. Figures 3 or 16), watercolor, and toner.

```
qmap(baylor, zoom = 14, source = "stamen",
  maptype = "watercolor")
```



```
qmap(baylor, zoom = 14, source = "stamen",
  maptype = "toner")
```



Figure 6: Stamen tile sets `maptype = "watercolor"` and `maptype = "toner"`

Stamen's terrain tile set is quite similar to Google's, but obviously the watercolor and toner tile sets are substantially different than any of the four




Google tile sets. The latter, for example, is ideal for black-and-white plotting.

Cloudmade Maps takes the tile styling even further by allowing the user to either (1) select among *thousands* of user-made sets or (2) create an entirely new style with a simple online editor where the user can specify colors, lines, and so forth for various types of roads, waterways, landmarks, etc., all of which are generated by CloudMade and accessible in **ggmap**. **ggmap**, through `get_map` (or `get_cloudmademap`) allows for both options. This is a unique feature of CloudMade Maps which really boosts their applicability and expands the possibilities with **ggmap**. The one minor drawback to using CloudMade Maps is that the user must register with CloudMade to obtain an API key and then pass the API key into `get_map` with the `api_key` argument. API keys are free of charge and can be obtained in a matter of minutes. Two low-light CloudMade map styles are seen in Figure 7.

Both Stamen Maps and CloudMade Maps are built using OpenStreetMap data. These data are contributed by an open community of online users in much the same way Wikipedia is—both are free, both are user-contributed, and both are easily edited. Moreover, OpenStreetMap has data not only on roadways and bodies of water but also individual buildings, fountains, stop signs and other apparent minutiae. The draw back is that (like Google Maps) not all locations are mapped with the same degree of precision. For example, entire lakes might be missing from the tile sets.

```
qmap(baylor, zoom = 14, maptype = 53428,
     api_key = api_key, source = "cloudmade")
```



```
qmap("houston", zoom = 10, maptype = 58916,
     api_key = api_key, source = "cloudmade")
```




Figure 7: Two out of thousands of user made CloudMade Maps styles. The top is comparable to Figures 4 and 6, and the bottom is the bodies of water in Figure 5

## The ggmap function

Once `get_map` has grabbed the map of interest, **ggmap** is ready to plot it. The result of `get_map` is a specially classed raster object (a matrix of colors as hexadecimal character strings) –

```
> paris <- get_map(location = "paris")
> str(paris)
chr [1:1280, 1:1280] "#C6DAB6" "#C2D6B3" "#C2D6B3" ...
- attr(*, "class")= chr [1:2] "ggmap" "raster"
- attr(*, "bb")='data.frame': 1 obs. of 4 variables:
..$ ll.lat: num 48.6
..$ ll.lon: num 1.91
..$ ur.lat: num 49.1
..$ ur.lon: num 2.79
```

The purpose of **ggmap** is to take the map from the raster object to the screen, and it fulfills this purpose by creating a **ggplot** object which, when printed, draws the desired map in the graphics device. This is illustrated in Figure 8.

While **ggmap** requires a **ggmap** object, it accepts a handful of other arguments as well—`extent`, `base_layer`, `maprange`, `legend`, `padding`, and `darken`. With none of these additional arguments, **ggmap** effectively returns the following **ggplot** object

```
ggplot(aes(x=lon, y=lat), data=fourCorners) +
  geom_blank() + coord_map("mercator") +
  annotation_raster(ggmap,
    xmin, xmax, ymin, ymax)
```

where `fourCorners` is the data frame resulting from applying `expand.grid` to the longitude and latitude

ranges specified in the `bb` attribute of the `ggmap` object. Thus, the default base layer of the `ggplot2` object created by `ggmap` is `ggplot(aes(x=lon,y=lat), data = fourCorners)`, and the default  $x$  and  $y$  aesthetic scales are calculated based on the longitude and latitude ranges of the map.




Figure 8: `ggmap(paris, extent = "normal")`

The `extent` argument dictates how much of the graphics device is covered by the map. It accepts three possible strings: `"normal"` shown in Figure 8, `"panel"` shown in Figures 13 and 15, and `"device"` shown in every other figure. `"normal"` situates the map with the usual axis padding provided by `ggplot2` and, consequently, one can see the panel behind it. `"panel"` eliminates this, setting the limits of the plot panel to be the longitude and latitude extents of the map with `scale_[x,y]_continuous(expand = c(0,0))`. `"device"` takes this to the extreme by eliminating the axes themselves with the new exported theme `nothing`.

`base_layer` is a call which substitutes the default base layer to the user's specification. Thus, in the above code the user can change `ggplot(aes(x=lon,y=lat), data=fourCorners)` to a different call. This is essential for faceting plots since the referent of `ggplot2` functions `facet_wrap` and `facet_grid` is the base layer. Since changing the base layer changes the base scales and therefore limits of the plot, it is possible that when the base layer is changed only part of the map is visible. Setting the `maprange` argument to `TRUE` (it defaults to `FALSE`) ensures that *the map* determines the  $x$  and  $y$  axis limits (longitude and latitude) via the `bb` attribute of the `ggmap` object itself, and not the `base_layer` argument.

The legend-related arguments of `ggmap` are `legend` and `padding`, and they are only applicable when `extent = "device"`. The `legend` argument de-

termines where a legend should be drawn on the map if one should be drawn. Its options are `"left"`, `"right"` (default), `"bottom"`, `"top"`, `"topleft"`, `"bottomleft"`, `"topright"`, `"bottomright"` and `"none"`. The first four draw the legend according to `ggplot2`'s normal specifications (without any axes); the next four draw the legend on top of the map itself similar to ArcGIS; and the last eliminates the legend altogether. `padding` governs how far from the corner the legend should be drawn when on top of the map.

The `darken` argument, a suggestion by Jean-Olivier Irsson, tints the map image. The default, `c(0,"black")`, indicates a fully translucent black layer, i.e. no tint at all. Generally, the first argument corresponds to an alpha blending (0 = invisible, 1 = opaque) and the second argument the color of the tint. If only a number is supplied to the `darken` argument `ggmap` assumes a black tint. The tint itself is made by adding a `geom_rect` layer on top of the map. An example is provided by Figure 3, where a black tint was added to the map to enhance the visibility of the points.

Since `ggmap` returns a `ggplot` object, the product of `ggmap` can itself act as a base layer in the `ggplot2` framework. This is an incredibly important realization which allows for the full range of `ggplot2` capabilities. We now illustrate many of the ways in which this can be done effectively through a case study of violent crime in downtown Houston, Texas.

## Data

Crime data were compiled from the Houston Police Department's website over the period of January 2010-August 2010. The data were lightly cleaned and aggregated using `plyr` and geocoded using Google Maps (to the center of the block, e.g., 6150 Main St.); the full data set is available in `ggmap` as the data set `crime`.

```
> str(crime)
'data.frame': 86314 obs. of 17 variables:
 $ time      : POSIXt, format: "2010-01-01 0..."
 $ date      : chr  "1/1/2010" "1/1/2010" "1..."
 $ hour      : int   0 0 0 0 0 0 0 0 0 0 ...
 $ premise   : chr  "18A" "13R" "20R" "20R" ...
 $ offense   : chr  "murder" "robbery" "aggr..."
 $ beat      : chr  "15E30" "13D10" "16E20" ...
 $ block     : chr  "9600-9699" "4700-4799" ...
 $ street    : chr  "marlive" "telephone" "w..."
 $ type      : chr  "ln" "rd" "ln" "st" ...
 $ suffix    : chr  "-" "-" "-" "-" ...
 $ number    : int   1 1 1 1 1 1 1 1 1 1 ...
 $ month     : Factor w/ 12 levels "january"...
 $ day       : Factor w/ 7 levels "monday" ...
 $ location  : chr  "apartment parking lot" ...
 $ address   : chr  "9650 marlive ln" "4750 ..."
 $ lon       : num  -95.4 -95.3 -95.5 -95.4 ...
 $ lat       : num  29.7 29.7 29.6 29.8 29.7...
```



Since we are only interested in violent crimes which take place downtown, we restrict the data set to those qualifiers. To determine a bounding box, we first use `gglocator`, a `ggplot2` analogue of base's `locator` function exported from `ggmap`. `gglocator` works not only for `ggmap` plots, but `ggplot2` graphics in general.

```
> # find a reasonable spatial extent
> qmap('houston', zoom = 13)
> gglocator(2)
      lon      lat
1 -95.39681 29.78400
2 -95.34188 29.73631

# only violent crimes
violent_crimes <- subset(crime,
  offense != "auto theft" &
  offense != "theft" & offense != "burglary")

# order violent crimes
violent_crimes$offense <- factor(
  violent_crimes$offense, levels =
    c("robbery", "aggravated assault",
      "rape", "murder"))

# restrict to downtown
violent_crimes <- subset(violent_crimes,
  -95.39681 <= lon & lon <= -95.34188 &
  29.73631 <= lat & lat <= 29.78400)
```

The longitude and latitude in the last few lines were obtained using the new exported function `gglocator`—a `ggplot2` analogue of the graphics function `locator`—on a larger map.

The analysis performed only concerns data on the violent crimes of aggravated assault, robbery, rape and murder. Note that while some effort was made to ensure the quality of the data, the data were only leisurely cleaned and the data set may still contain errors.

## Analysis – ggmap in action

The first step we might want to take is to look at where the individual crimes took place. Modulo some simple `ggplot2` styling changes (primarily in the fonts and key-styles of the legends via `ggplot2`'s `guide` function), the following code produces the spatial bubble chart in Figure 9.

```
theme_set(theme_bw(16))
HoustonMap <- qmap("houston", zoom = 14,
  color = "bw", legend = "topleft")

HoustonMap +
  geom_point(aes(x = lon, y = lat,
    colour = offense, size = offense),
    data = violent_crimes)
```




Figure 9: Violent crime bubble chart of downtown Houston

One of the problems with the bubble chart is overplotting and point size—we can't really get a feel for what crimes are taking place and where. One way around this is to bin the points and drop the bins which don't have any samples in them. The result (Figure 10) shows us where the crimes are happening at the expense of knowing their frequency.

```
HoustonMap +
  stat_bin2d(
    aes(x = lon, y = lat, colour = offense,
      fill = offense),
    size = .5, bins = 30, alpha = 1/2,
    data = violent_crimes)
```




Figure 10: Contour plot of violent crimes by offense type

Figure 10 is the first time we really begin to see the power of having the maps in the **ggplot2** framework. While it is actually not a very good plot, it illustrates the practical advantage of the **ggplot2** framework with the contextual information of the map—splitting the data frame `violent_crimes` into chunks based on the offense variable, binning the points of each, and aggregating back into one data set to plot is all done entirely behind the scenes by **ggplot2**. **ggplot2** has several such canned procedures.

What about violent crime in general? If we neglect the type of offense, we can get a good idea of the spatial distribution of violent crimes by using a contour plot. Since the map image itself is based on **ggplot2**'s new `annotation_raster`, which doesn't have a fill aesthetic, we can access the fill aesthetic to make a filled contour plot.

```
houston <- get_map("houston", zoom = 14)
HoustonMap <- ggmap("houston",
  extent = "device", legend = "topleft")

HoustonMap +
  stat_density2d(
    aes(x = lon, y = lat, fill = ..level..,
      alpha = ..level..),
    size = 2, bins = 4, data = violent_crimes,
    geom = "polygon")
```




Figure 11: Filled contour plot of violent crimes

These kinds of overlays can be incredibly effective; however, their ability to communicate information can be hindered by the fact that the map overlay can be visually confused with the map itself. This is particularly common when using colored maps. To get around this problem the `inset` function can be used to insert map insets containing the overlay on a white background. The viewing is made easier by the exported function `theme_inset`.

```
overlay <- stat_density2d(
  aes(x = lon, y = lat, fill = ..level..,
    alpha = ..level..),
  bins = 4, geom = "polygon",
  data = violent_crimes)
```

```
HoustonMap + overlay + inset(
  grob = ggplotGrob(ggplot() +
    overlay + theme_inset()),
  xmin = -95.35836, xmax = Inf,
  ymin = -Inf, ymax = 29.75062
)
```




Figure 12: Filled contour plot with inset

The image indicates that there are three main hotspots of activity. Each of these three correspond to locations commonly held by Houstonians to be particularly dangerous locations. From east to west, the hotspots are caused by 1. a county jail which releases its inmates twice daily, who tend to loiter in the area indicated, 2. a commercial bus station in an area of substantial homelessness and destitution, and 3. a prostitution hotspot in a very diverse and pedestrian part of town.

In addition to single plots, the `base_layer` argument to `ggmap` or `qmap` allows for faceted plots. This is particularly useful for spatiotemporal data with discrete temporal components (day, month, season, year, etc.).

```
houston <- get_map(location = "houston",
  zoom = 14, color = "bw", source = "osm")

HoustonMap <- ggmap(houston,
  base_layer = ggplot(aes(x = lon, y = lat),
    data = violent_crimes))

HoustonMap +
  stat_density2d(aes(x = lon, y = lat,
```



```
fill = ..level.., alpha = ..level..),
  bins = 5, geom = "polygon",
  data = violent_crimes) +
  scale_fill_gradient(low = "black",
    high = "red") +
  facet_wrap(~ day)
```




Figure 13: Faceted filled contour plot by day

This last plot displays one of the known issues with contour plots in **ggplot2**—a “clipping” or “tearing” of the contours. Aside from that fact (which will likely be fixed in subsequent **ggplot2** versions), we can see that in fact most violent crimes happen on Monday, with a distant second being Friday. Friday’s pattern is easily recognizable—a small elevated dot in the downtown bar district and an expanded region to the southwest in the district known as midtown, which has an active nightlife. Monday’s pattern is not as easily explainable—it may be that more jail inmates are released on Monday who had weekend stays.

## ggmap’s utility functions

**ggmap** has several utility functions which aid in spatial exploratory data analysis.

### geocode

The ability to move from an address to a longitude/latitude coordinate is virtually a must for visualizing spatial data. Unfortunately however, the process is almost always done outside R by using a proper geographic information system (GIS), saving the results, and importing them into R. The `geocode` function simplifies this process to a single line in R.

`geocode` is a vectorized function which accepts character strings and returns a data frame of geographic information. In the default case of output

= “simple”, only longitudes and latitudes are returned. These are actually Mercator projections of the ubiquitous unprojected 1984 world geodetic system (WGS84), a spheroidal earth model used by Google Maps. When output is set to “more”, a larger data frame is returned which provides much more Google Geocoding information on the query :

```
> geocode("baylor university", output = "more")
      lon    lat    type loctype
1 -97.11441 31.54872 university approximate
  address north south east
1 [long address] 31.55823 31.53921 -97.0984
  west postal_code country
1 -97.13042      76706 united states
  administrative_area_level_2
1                               mcclennan
  administrative_area_level_1 locality street
1                               texas    waco s 5th st
  streetNo point_of_interest
1      1311                <NA>
```

In particular, administrative bodies at various levels are reported. Going further, setting `output = "all"` returns the entire JavaScript Object Notation (JSON) tree given by the Google Geocoding API parsed by **rjson** (Couture-Beil, 2011).

The Geocoding API has a number of request limitations in place to prevent abuse. An unspecified short-term rate limit is in place (see `mapdist` below) as well as a 24-hour limit of 2,500 requests. These are monitored to some extent by the hidden global variable `.GoogleGeocodeQueryCount` and exported function `geocodeQueryCheck`. `geocode` uses these to monitor its own progress and will either (1) slow its rate depending on usage or (2) error if the query limit is exceeded. Note that `revgeocode` shares the same request pool and is monitored by the same variable and function. To learn more about the Google Geocoding, Distance Matrix, and Directions API usage regulations, see the websites listed in the bibliography.

### revgeocode

In some instances it is useful to convert longitude/latitude coordinates into a physical address. This is made possible (to the extent to which it is possible) with the `revgeocode` function which also relies on the Google Geocoding API.

```
> gc <- geocode("baylor university")
> (gc <- as.numeric(gc))
[1] -97.11441 31.54872
> revgeocode(gc)
[1] "S 1st St, Baylor University, Waco, TX
    76706, USA"
```

Like `geocode`, more output can be provided as well –

```
> revgeocode(gc, output = "more")
      address route establishment
```

```

1 [long address] S 1st St Baylor University
  neighborhood locality
1 Baylor Waco
  administrative_area_level_2
1 McLennan
  administrative_area_level_1 country
1 Texas United States
  postal_code
1 76706

```

Thus, in addition to the physical *where* of a reverse geocode (i.e., the address), `revgeocode` can report the *what* at various levels of granularity. Finally, an `output = "all"` option is available which returns the entire JSON list tree reported by Google.

#### mapdist

The ability to compute real distances in a spatial setting is another invaluable commodity which typically sends analysts to a GIS. Using the Google Distance Matrix API, **ggmap** is able to provide distances for Google-determined routes for driving, bicycling, or walking. In addition to the distances, Google reports estimated travel durations as well. The full output is placed in an easy-to-use data frame. For example,

```

> from <- c("houston", "houston", "dallas")
> to <- c("waco, texas", "san antonio",
+ "houston")
> mapdist(from, to)
      from      to      m      km      miles
1 houston waco, texas 298004 298.004 185.1797
2 houston san antonio 320764 320.764 199.3227
3 dallas  houston 387389 387.389 240.7235
  seconds minutes  hours
1  11907   198.45  3.307500
2  11997   199.95  3.332500
3  14592   243.20  4.053333

```

The default mode of transportation is driving; however, the other modes are also available. The input forms of `from` and `to` can be either physical addresses (ideal), lazy ("the white house"), or geographic coordinates (which are reverse geocoded). While the output defaults to the data frame format seen above, setting `output = "all"` provides the full JSON tree from Google.

The Distance Matrix API limits users to 100 requests per query, 100 requests per 10 seconds, and 2500 requests per 24 hours. To the extent to which these can be easily monitored, the exported function `distQueryCheck` helps the user keep track of their remaining balance of queries. It relies on the hidden global variable `.GoogleDistQueryCount` –

```

> distQueryCheck()
2495 distance queries remaining.
> .GoogleDistQueryCount

```

<sup>2</sup>This was inspired by the beautiful work of J. Cheshire available at <http://spatialanalysis.co.uk/2012/02/great-maps-ggplot2/>.

```

      time      url elements
1 2012-03-16 00:12:11 [url used]      1
2 2012-03-16 00:16:10 [url used]      2

```

If the user exceeds the limitations, `mapdist` either (1) pauses until the short-term request limit has lapsed or (2) errors if no queries are remaining. Thus, it is almost identical to the mechanism in place for geocoding. If the user believes this to be incorrect, an override is available with the `mapdist` specification `override_limit = TRUE`.

The data frame output of `mapdist` is very convenient for use with **ggplot2**. An example is provided by Figure 14, where travel times from one location ("My Office") to several nearby locations are (1) determined using `mapdist`, (2) binned into categories using `cut`, and then (3) plotted using a combination of `qmap`, `geom_text`, and `geom_rect` with the fill aesthetic set to the category of travel time. The full code is in the examples section of the documentation of `ggmap`.




Figure 14: Distances by time provided by `mapdist`

#### route

The `route` function provides the map distances for the sequence of "legs" which constitute a route between two locations. Each leg has a beginning and ending longitude/latitude coordinate along with a distance and duration in the same units as reported by `mapdist`. The collection of legs in sequence constitutes a single route (path) most easily plotted with `geom_leg`, a new exported **ggplot2** geom which is simply `geom_segment` with rounded ends.<sup>2</sup>

A nice illustration of plotting routes with `geom_leg` can be seen in Figure 15 where three routes are plotted between the same two locations. These can be obtained using the `alternatives =`



TRUE specification in `route.alternatives` requests more than one route from the origin to the destination; the returned value is again a data frame with an additional variable which serves as a route identifier (A, B, C, etc.).

Like map distances, there are restrictions on the limit of routes which can be requested in a given period of time as well. The number of queries left is monitored by the `.GoogleRouteQueryCount` variable with the `routeQueryCheck` function.

## Plotting shape files

As a final example which is perhaps too common to ignore, plotting shape files with **ggmap** is a breeze and can be done in several ways. The easiest way is to convert the shape file to a data frame with `fortify` (**ggplot2**) and then add a point/path/polygon layer to the map, depending on what the contents of the shape file are (note that `fortify` does not yet have methods for all shape files). Additional layers can be added by simply layering on more `geom` layers. Figure 16 shows a basic example of plotting the U.S. Census 2000 census tracts along with complete code (U.S. Census Bureau, 2001).

## Conclusion and future directions

Building on top of **ggplot2**, **ggmap** provides several new useful tools for visualizing spatial data. Theoretically speaking, the layered grammar of graphics attempts to enforce plotting consistency and therefore good plotting practice. Practically speaking, building **ggmap** on **ggplot2** makes the result even better as the full range of **ggplot2** capabilities can be brought to bear.

There are a number of future directions in store for **ggmap**. The new **osmar** package integrates R and the OpenStreetMap data structures with which OpenStreetMap maps, Stamen Maps, and Cloud-Made Maps are rendered, thereby opening a floodgate of possibilities for plotting geographic objects on top of maps or satellite imagery all within R using **ggmap** (Schlesinger and Eugster, 2012). Alternatively, integration with other spatial packages in R could provide several incredibly useful practical tools for spatial data analysis. Finally, the Google Elevation API and Places API provide additional interesting frontiers which can be incorporated into the **ggmap** framework just like the other Google APIs to give users additional capabilities though freely available geographical data.

The authors would like to thank Jean-Olivier Irisson for his comments.

## Bibliography

R.S. Bivand, E.J. Pebesma, and V. Gomez-Rubio. *Applied spatial data analysis with R.*, Springer, New York The R Journal Vol. X/Y, Month, Year

York, 2008. URL <http://www.asdar-book.org/>.

A. Couture-Beil. *rjson: JSON for R.*, R package version 0.2.6. URL <http://CRAN.R-project.org/package=rjson>.

Google, Inc. *The Google Geocoding API.* URL <http://code.google.com/apis/maps/documentation/geocoding/>.

Google, Inc. *The Google Distance Matrix API.* URL <http://code.google.com/apis/maps/documentation/distancematrix/>.

Google, Inc. *The Google Directions API.* URL <https://developers.google.com/maps/documentation/directions/>.

M. Loecher and Sense Networks. *RgoogleMaps: Overlays on Google map tiles in R.*, R package version 1.1.9.3. URL <http://CRAN.R-project.org/package=RgoogleMaps>.

E.J. Pebesma and R.S. Bivand. Classes and methods for spatial data in R. *R News*, 5(2), 2005. URL <http://cran.r-project.org/doc/Rnews/>.

T. Schlesinger and Manuel J. A. Eugster. *osmar: OpenStreetMap and R.*, R package version 1.1-3. URL <http://CRAN.R-project.org/package=osmar>.

U.S. Census Bureau, Geography Division, Cartographic Products Management Branch. *Census 2000: Census Tract Cartographic Boundary Files.* URL <http://www.census.gov/geo/www/cob/tr2000.html>.

H. Wickham. *ggplot2: elegant graphics for data analysis.*, Springer, New York, 2009.

H. Wickham. A layered grammar of graphics. *Journal of Computational and Graphical Statistics*, 19(1):3–28, 2010.

H. Wickham. The Split-Apply-Combine Strategy for Data Analysis. *Journal of Statistical Software*, 40(1):1–29, 2011. URL <http://www.jstatsoft.org/v40/i01/>.

L. Wilkinson. *The Grammar of Graphics.*, 2nd ed., Springer, New York, 2005.

David Kahle  
Baylor University  
Department of Statistical Science  
One Bear Place #97140  
Waco, TX 77005  
[david\\_kahle@baylor.edu](mailto:david_kahle@baylor.edu)

Hadley Wickham  
Rice University  
Department of Statistics, MS 138  
6100 Main St.  
Houston, TX 77005  
[hadley@rice.edu](mailto:hadley@rice.edu)




Figure 15: Three routes returned by route plotted with `geom_leg`

```
download.file('http://www.census.gov/geo/cob/bdy/tr/tr00shp/tr48_d00_shp.zip', destfile = 'census.zip')
unzip('census.zip'); library(maptools); library(gpclib); library(sp); gpclibPermit()
shapefile <- readShapeSpatial('tr48_d00.shp', proj4string = CRS("+proj=longlat +datum=WGS84"))
data <- fortify(shapefile)
qmap('texas', zoom = 6, maptype = 'satellite') +
  geom_polygon(aes(x = long, y = lat, group = group), data = data,
    colour = 'white', fill = 'black', alpha = .4, size = .3)
```




Figure 16: Plotting shape files – Census tracts in Texas from the 2000 U.S. Census